Administration Administration Administration

# **Administration**

The administration function is used to maintain Object Handler workplans.

For information on workplans and the syntax that applies, refer to the sections Workplans and Commands.

#### Note

You can set the default library for workplans in the SYSOBJH profile using the option Workplan-Library (see SYSOBJH Profile).

The Administration screen provides the following options:

- List the available Workplans in the Workplan Library
- Create a new Workplan
- Change the Workplan Library

# List the available Workplans in the Workplan Library

This function is used to list all Natural objects of the type Text available in the workplan library and to select all workplans available.

Below is an example of how to invoke and execute the function:

### To list workplans

- On the Administration screen, select "List the available Workplans in the Workplan Library" and press ENTER, or press the corresponding PF key.
  - The List Workplans screen appears listing all workplans available.
  - If the Natural object of the type Text is a workplan, the type of workplan and the first 50 bytes of the workplan description are listed. Press PF5 to display additional information.
- Select a workplan. See also Columns and Commands in the section Workplans.

# Create a new Workplan

This function invokes the "Create a new Workplan" screen where you can specify the type of the new workplan and choose the option Free Format Editing (see also the direct commands SET FREE ON and SET FREE OFF in Commands for CUIs).

With Free Format Editing set to OFF (not activated), for workplans of the types OPTION, PARAMETER and SELECTION, screens with input fields are provided.

If the option Free Format Editing set to ON, or if you create a workplan of another type, you will get a map with an edit area. Enter the contents of the workplan; see the syntax as described in the section Commands.

# Change the Workplan Library

This function is used to change the workplan library. All workplans must be stored in a workplan library as otherwise data processing cannot be controlled by workplans, such as the function Select OPTION Workplan.

The "Change Workplan Library" screen provides the following fields:

Copyright Software AG 2001

Change the Workplan Library Administration

Library	The name of the workplan library. Default is the library WORKPLAN.
Select Library	Displays a list of the workplan libraries available: see also Library Selection.
PF4/SeLib	
DBID/FNR	Specifies the database ID (DBID) and file number (FNR) where the workplan library resides. If no values are specified, the FUSER or FNAT system file is used.